

PRODUCT DATASHEET

Last information update: May 2023




ARKOS

0820W100

Architectural LED floodlight for outdoor applications


Technical Features

Power	100W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	4,000 lm ±10%
Light distribution type	symmetrical / elliptical
Beam angle	15°, 20°, 30°, 45° / 15°x60°
Light colour / CCT	RGBCLAW
CRI	-
Source type	LED (7-IN-1)
LED number	16
MacAdam step	-
Power supply	Built-in
Control	DMX512
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Wiring

Power input cable OPEN END 500mm
 DMX input cable MALE connector 500mm
 DMX output cable FEMALE connector 500mm



Construction

Fluorocarbonate powder painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C















Installation

Surface mounted with adjustable base.

Finish Colours

RAL9023 as standard colour, other RAL colours on request.

Optional Accessories

	<p>built-in anti-glare accessory for improved visual comfort *can not be ordered separately</p>	<p>honeycomb</p>	
	<p>anti-glare accessory for improved visual comfort *can not be ordered separately</p>	<p>anti-glare glass</p>	
	<p>mounting accessory *can not be ordered separately</p>		<p>U-bracket</p>
	<p>mounting accessory for Ø 48mm poles *can not be ordered separately</p>		<p>pole adapter</p>
	<p>mounting accessory for Ø 114mm poles *can not be ordered separately</p>		<p>pole clamp</p>
	<p>mounting accessory for Ø 67~325mm T>=4 poles *can not be ordered separately</p>		<p>pole plate</p>
	<p>mounting accessory for Ø 168~268mm trees *can not be ordered separately</p>		<p>strap</p>
	<p>with female 4-pin waterproof connector for DMX * specify cable length to complete order</p>	<p>leader cable</p>	
	<p>with male and female 4-pin waterproof connector for DMX * specify cable length to complete order</p>	<p>extension cable</p>	

Ordering Information

example: **0820W100.0015.7130K.01+A1**

0820W100 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
ARKOS 100W	0015 15°	7130K RGBCLA+3000K	01 RAL9023	A1 honeycomb
	0020 20°	7140K RGBCLA+4000K		A2 anti-glare glass
	0030 30°			A3 U-bracket
	0045 45°			A4 pole adapter
	1560 15°x60°			A5 pole clamp
				A6 pole plate
				A7 strap
				LC4 leader cable
				EC4 extension cable