

## PRODUCT DATASHEET

Last information update: May 2023




### ARC-SIDE

1915W2X2

Inground LED marker light for outdoor applications

#### Technical Features

Power	2x2W
Input voltage	DC24V ( constant voltage )
Insulation class	III
Delivered flux	240 lm ±10%
Light distribution type	symmetrical, 2-emission
Beam angle	60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	2
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



#### Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Wiring

Power input cable OPEN END 500mm



#### Installation

Ground recessed with recessed box.

#### Finish Colours

Stainless steel as standard colour. RAL colours on request.

**Ordering Information**

example: **1915W2X2.0060.2780.01**

1915W2X3 ·  ·  ·  +

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 2x2W 2-EMISSION	<b>0060</b> 60°	<b>2780</b> 2700K RA80	<b>01</b> stainless steel
		<b>3080</b> 3000K RA80	
		<b>4080</b> 4000K RA80	

## PRODUCT DATASHEET

Last information update: May 2023




### ARC-SIDE

1915W2X2(220V)

Inground LED marker light for outdoor applications

#### Technical Features

Power	2x2W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	240 lm ±10%
Light distribution type	symmetrical, 2-emission
Beam angle	60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	2
MacAdam step	5
Power supply	built-in
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Walk over	yes
Drive over	yes
Lifetime	50,000 hours Ta=25°C



#### Construction

Stainless steel body, engineering plastic recessed box, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Wiring

Power input cable OPEN END 500mm



#### Installation

Ground recessed with recessed box.

#### Finish Colours

Stainless steel as standard colour. RAL colours on request.

**Ordering Information**

example: **1915W2X2(220V).0060.2780.01**

1915W2X2(220V) ·  ·  ·  +

product	beam angle	light colour / CCT	finish colour
ARC-SIDE 2x2W 2-EMISSION	<b>0060</b> 60°	<b>2780</b> 2700K RA80	<b>01</b> stainless steel
		<b>3080</b> 3000K RA80	
		<b>4080</b> 4000K RA80	