

PRODUCT DATASHEET

Last information update: May 2023



BLADE M

2020W20

Light effect LED luminaires for illuminating window reveals

Technical Features

Power	20W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	600 lm ±10%
Light distribution type	elliptical
Beam angle	8°x120°
Light colour / CCT	RGBW
CRI	-
Source type	LED
LED number	8
MacAdam step	-
Power supply	Not included
Control	DMX512
Protection index	IP65
Impact resistance	IK05
Lifetime	50,000 hours Ta=25°C



Construction

Fluorocarbon painted die-cast aluminum body, tempered glass, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation


Surface mounted with base (non-adjustable).

Finish Colours


RAL9023 as standard colour, other RAL colours on request.

Wiring

Power/DMX input cable MALE connector 500mm
Power/DMX output cable FEMALE connector 500mm




Optional Accessories



with female 6-pin waterproof connector for DMX
* specify cable length to complete order

leader cable



with male and female 6-pin waterproof connector for DMX
* specify cable length to complete order

extension cable

Ordering Information

example: 2020W20.RGB30K.01+LC6

2020W20 · [] · [] · [] + []

product	light colour / CCT		finish colour		accessory	
BLADE M 20W	RGB30K	RGB+3000K	01	RAL9023	LC6	leader cable
	RGB40K	RGB+4000K			EC6	extension cable