

## PRODUCT DATASHEET

Last information update: May 2023




### CUBE 2.0

0822W45

Architectural LED floodlight for outdoor applications

#### Technical Features

Power	45W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,580 lm ±10%
Light distribution type	symmetrical
Beam angle	ultra spot 2°
Light colour / CCT	RGBW
CRI	-
Source type	LED
LED number	9
MacAdam step	-
Power supply	Built-in
Control	DMX512
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



#### Construction

Fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

#### Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

#### Installation


Surface mounted with adjustable base.

#### Finish Colours












RAL9023 as standard colour, other RAL colours on request.


#### Wiring

Power input cable OPEN END 500mm  
 DMX input cable MALE connector 500mm  
 DMX output cable FEMALE connector 500mm




Optional Accessories

	<p>built-in anti-glare accessory for improved visual comfort *can not be ordered separately</p>		<p>honeycomb</p>
	<p>anti-glare accessory for improved visual comfort *can not be ordered separately</p>		<p>visor</p>
	<p>mounting accessory *can not be ordered separately</p>		<p>U-bracket</p>
	<p>mounting accessory for Ø 48mm poles *can not be ordered separately</p>		<p>pole adapter</p>
	<p>mounting accessory for Ø 114mm poles *can not be ordered separately</p>		<p>pole clamp</p>
	<p>mounting accessory for Ø 67~325mm T&gt;=4 poles *can not be ordered separately</p>		<p>pole plate</p>
	<p>mounting accessory for Ø 168~268mm trees *can not be ordered separately</p>		<p>strap</p>
	<p>mounting accessory *can not be ordered separately</p>		<p>spike</p>



with female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

leader cable



with male and female 4-pin waterproof connector for DMX  
\* specify cable length to complete order

extension cable

### Ordering Information

example: **0822W45.0002.RGB30K.01+A1**

0822W45 · [ ] · [ ] · [ ] + [ ]

product	beam angle	light colour / CCT	finish colour	accessory
CUBE 2.0 45W ULTRA SPOT	<b>0002</b> 2°	<b>RGB30K</b> RGB+3000K <b>RGB40K</b> RGB+4000K	<b>01</b> RAL9023	<b>A1</b> honeycomb <b>A2</b> visor <b>A3</b> U-bracket <b>A4</b> pole adapter <b>A5</b> pole clamp <b>A6</b> pole plate <b>A7</b> strap <b>A8</b> spike <b>LC4</b> leader cable <b>EC4</b> extension cable