

PRODUCT DATASHEET

Last information update: May 2023




YORK M 1000MM

2504W100

Architectural linear LED wallwasher for outdoor applications

Technical Features

Power	100W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	5,000 lm ±10%
Light distribution type	symmetrical
Beam angle	ultra spot 2.5°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	20
MacAdam step	5
Power supply	included
Control	ON/OFF
Protection index	IP66
Impact resistance	IK07
Lifetime	50,000 hours Ta=25°C



Construction

Anodized extruded aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable bracket.

Finish Colours


Alumunim as standard colour, RAL colours on request.

Wiring

Power input cable OPEN END 500mm




Optional Accessories




anti-glare accessory for improved visual comfort
*can not be ordered separately

honeycomb



anti-glare accessory for improved visual comfort
*can not be ordered separately



visor

Ordering Information

example: **2504W100.0002.2780.01+A1**

2504W100 · [] · [] · [] + []

product	beam angle	light colour / CCT	finish colour	accessory
YORK M 1000MM 100W ULTRA SPOT	0002 2.5°	2780 2700K RA80	01 aluminum	A1 honeycomb
		3080 3000K RA80		A2 visor
		4080 4000K RA80		