

PRODUCT DATASHEET

Last information update: May 2023



BLADE M

2020W20

Light effect LED luminaires for illuminating window reveals

Technical Features

Power	20WW
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	1,000 lm ±10%
Light distribution type	elliptical
Beam angle	8°x120°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	8
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP65
Impact resistance	IK05
Lifetime	50,000 hours Ta=25°C

Construction

Fluorocarbon painted die-cast aluminum body, tempered glass, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with base (non-adjustable).

Finish Colours

RAL9023 as standard colour, other RAL colours on request.

Wiring

Power input cable OPEN END 500mm



Ordering Informationexample: **2020W20.2780.01**2020W20 ·  ·  ·  + 

product	light colour / CCT	finish colour
BLADE M 20W	2780 2700K RA80	01 RAL9023
	3080 3000K RA80	
	4080 4000K RA80	