


PRODUCT DATASHEET

Last information update: Mar. 2025



ARC-SIDE-1

In-ground LED marker light for outdoor applications

1915W3

Technical Features

Power	3W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	180 lm ±10%
Light distribution type	Symmetrical
Beam angle	60°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	1
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP67
Impact resistance	IK10
Lifetime	50,000 hours Ta=25°C

Construction

Die-cast aluminum body, stainless steel trim, polycarbonate optical lenses, plastic recessed box.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Ground recessed with recessed box (standard).

Finish Colours

Trim in Stainless Steel (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm



Ordering Information

example: 1915W3.0060.2780.01

1915W3 .  .  . 

product	beam angle		light colour / CCT		finish colour
ARC-SIDE-1-3W	0060	60°	2780	2700K RA80	01 stainless steel
1 light emission			3080	3000K RA80	
			4080	4000K RA80	