



PRODUCT DATASHEET

Last information update: Mar. 2025



Wiring

Power input cable OPEN END 1,000 mm
DMX input cable MALE connector 1,000 mm
DMX output cable FEMALE connector 1,000 mm



DAN LITE

1913W30(0.3)

Adjustable in-ground LED wallwasher for outdoor applications

Technical Features

Power	30W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,350 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	9°, 15°, 20°, 30°, 45° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED (4-IN-1)
LED number	5
MacAdam step	-
Power supply	Built-in
Control	DMX512 (built-in DMX decoder)
Protection index	IP67
Impact resistance	IK10
Lifetime	50,000 hours Ta=25°C

Construction

Aluminum body, stainless steel trim, tempered glass cover, PC optical lenses, aluminum recessed box.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C


Installation

Ground recessed with recessed box (standard).

Finish Colours


Trim in Stainless Steel (standard). Other RAL colours on request.

Optional Accessories




honeycomb louvre
*can not be ordered separately

A02




anti-glare grille
*can not be ordered separately

A03




anti-slip glass
*can not be ordered separately

A18



leader cable with female 4-pin waterproof connector for Power/DMX
* specify cable length to complete order

LC4



extension cable with male and female 4-pin waterproof connector for Power/DMX
* specify cable length to complete order

EC4

Ordering Information

example: 1913W30(0.3).0009.4130K.01+A02

1913W30(0.3) · · · +

product	beam angle		light colour / CCT		finish colour		accessory	
DAN LITE 30W (300MM)	0009	9°	4130K	RGB+3000K	01	stainless steel	A02	honeycomb louvre
	0015	15°	4140K	RGB+4000K			A03	anti-glare grille
	0020	20°					A18	anti-slip glass
	0030	30°					LC4	leader cable
	0045	45°					EC4	extension cable
	1560	15°x60°						