

PRODUCT DATASHEET

Last information update: Mar. 2025



DELTA-48

Linear LED wallwasher for outdoor applications

0819W300

Technical Features

Power	300W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	24,000 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	6°, 12°, 20°, 30°, 45°, 60° / 10°x70°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	48
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant fluorocarbon painted extruded aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable bracket (standard).

Finish Colours


RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm




Optional Accessories




honeycomb louvre
*can not be ordered separately

A02



anti-glare visor
*can not be ordered separately



A06

Ordering Information

example: 0819W300.0006.2780.01+A02

0819W300 · [] · [] · [] + []

product	beam angle		light colour / CCT		finish colour		accessory	
DELTA-48-300W	0006	6°	2780	2700K RA80	01	RAL9023	A02	honeycomb louvre
	0012	12°	3080	3000K RA80			A06	anti-glare visor
	0020	20°	4080	4000K RA80				
	0030	30°						
	0045	45°						
	0060	60°						
	1070	10°x70°						